



Structural spanning & self supporting.

See SSR24 Section Properties page & Load Table.

See SSR24 Design Manual for additional technical information and details.



MINIMUM 1/4:12 PITCH

Available as a Floating Clip System. Hand/mechanical seaming required.

Factory applied sealant along underside of receiving edge.

Thermal roof system with variable depth floating clips. Minimum 2" insulation recommended. Solar, Fall Arrest & snow management attachment systems available.

The steel used to manufacture SSR24 sheets, meets or exceeds the following specifications and reference standards:

ASTM A792/A792M, 55% Aluminum-Zinc Alloy-Coated (Galvalume) Steel Sheet with coating designation AZM150 [AZ50] for Painted Galvalume and AZM 165 [AZ55] Plain Galvalume sheets.

CSSBI 20M-17, Standard for Sheet Steel Cladding for Architectural, Industrial and Commercial Building Applications.

CSSBI S8-2008, Quality and Performance Specification for Prefinished Sheet Steel Used for Building Products.

CSA-S136-16, North American Specification for the Design of Cold-Formed Steel Structural Members.

		Gauge(s)					Gauge(s)					Gauge(s)		
Classic/Comm	Colour Code	24	22		Classic/Comm	Colour Code	24	22		Classic/Comm	Colour Code	24	22	
Antique Linen	8696				Deep Water Green	8684				Metro Brown	8228			
Black	8262				Galvalume	2	•			Pacific Turquoise	8258			
Bone White	8273	•	•		Galvanized	1				Regent Grey	8730	•		
Bright Red	8386				Gold	8276				Royal Blue	8790			
Bright White	8783	•			Heron Blue	8330				Sapphire Blue	8261			
Buckskin	9202				Hickory Moss	9368				Slate Blue	8260	•		
Burgundy	8011				Int'l Orange	8234				Stone Grey	8305	•	•	
Cambridge White	8695				Iron Ore	8614				Tan	8315	•	•	
Charcoal	8306	•	•		Ivory	8802				Tile Red	8259			
Coffee	8326	•			Light Stone	9367				Whistler Green	8093			
Dark Brown	8229				Medium Green	8329				White White	8317	•		
Dark Red	8250				Melcher's Green	8307								

Textured	Colour Code	24	22		Textured	Colour Code	24	22		Exotic	Colour Code	24	22	
Chocolate Brown	6034				Jet Black	6039				Copper Penny	2005			
Chrome Green	6037				Oxide Red	6042				Dark Zinc	1430			
Graphite Grey	6035				Sepia Brown	6041				Rustic Red	1426			

Wood Grain	Colour Code	24	22		Wood Grain	Colour Code	24	22					
Frontier Espresso	4100				Frontier Cedar	4101							

Product Description	Grade(s)	lbs./Lin. Ft.	Additional Information
24 Gauge Plain Galvalume	50	2.35	Please contact your nearest location for availability and minimum/maximum lengths. Extended lead time may be required. See Westman Steel Colour Chart for complete range. Contact for custom colour & specialty coating option.
24 Gauge Coloured	50	2.40	
22 Gauge Plain Galvalume	50	2.93	
22 Gauge Coloured	50	2.93	

Colour availability can vary by branch and may result in longer lead times.
Additional crating and freight charges may apply.